


CONNETTORE FEMMINA
A MODULI

FEMALE CONNECTOR
MODULES

CONNECTEUR FEMELLE
ELEMENTS

BUCHSENLEISTE
ANREIHBAR



Corpo isolante Verde	Insulating body Green	Corps isolant Vert	Isolierkörper Grün	PA68 UL94VO
Vite	Screw	Vis	Schraube	M3-C8R+Zn
Morsetto	Clamp	Borne	Klemmkörper	Cu Zn40 Pb2+Ni
Contatto	Pin	Contacte	Kontakt	CuSn7+Sn
Coppia di torsione	Testing torque	Couple de serrage	Zul. Drehmoment	0,5 Nm
Sezione	Section	Section	Querschnitt	2,5 mm ²
Vite imperdibile	Captive screw	Vis imperdable	Schraube unverlierbar	-
Corrente nominale	Nominal current	Courant nominal	Strombelastbarkeit	12 A
Tensione	Voltage	Tension	Betriebsspannung	450/750 V
Temperatura	Temperature	Température	Temperatur	85°C
Grado di protezione	Protection index	Degré de protection	Schutzklasse	IP00
Resistenza di isolamento	Insulation resistance	Résistance d'isolement	Isolationswiderstand	≥ 5 MΩ
Rigidità dielettrica	Dielectric strength	Rigidité diélectrique	Durchschlagsfestigkeit	≥ 2500 Vac/60"

Ref. EN 60998-1

P	p